

#### WHERE TO USE

Cleaning of all surfaces not previously treated with graffiti-resistant protection against conventional spray-paints.

# Some application examples

Removal of graffiti from:

- all types of natural stone facings;
- brick or concrete block facings;
- · concrete facings;
- unpainted renders;
- unpainted metal surfaces;
- areas where high-pressure cleaning is not practical.

#### **TECHNICAL CHARACTERISTICS**

**WallGard Graffiti Remover Gel** is a gel detergent based on a formula developed in MAPEI's own laboratories.

**WallGard Graffiti Remover Gel** removes all types of graffiti without damaging the underlying surface simply by spraying with a high pressure cleaner.

Its gelatinous consistency enables WallGard

**Graffiti Remover Gel** to remain on the surface of the graffiti without transporting the stain beneath the surface.

**WallGard Graffiti Remover Gel** works in 5 to 10 minutes, after which time it can be removed with water.

#### **RECOMMENDATIONS**

- Do not dilute WallGard Graffiti Remover Gel with solvents or water.
- Do not use WallGard Graffiti Remover Gel to remove residues and adhesives from the substrate.
- Do not use **WallGard Graffiti Remover Gel** to remove dirt deposited by smog.
- Do not use WallGard Graffiti Remover Gel on painted surfaces.

# **HOW TO USE Preparing the substrate**

No preparation is required.

### **Preparing the product**

WallGard Graffiti Remover Gel is ready to use and should not be diluted with water or solvents.

# WallGard Graffiti Remover Gel



Applying WallGard Graffiti Remover Gel with a brush



Cleaning with an abrasive pad



Cleaning with running water



Rinsing graffiti away after scrubbing surface with WallGard Graffiti Remover Gel and brush

## **Applying the product**

Apply **WallGard Graffiti Remover Gel** with a brush onto the graffiti or drawing.

Let stand 5 to 10 minutes and then remove the gel with a high-pressure cleaner.

In areas where using a high-pressure cleaner is not practical, **WallGard Graffiti Remover Gel** can be removed with tap water and a stiff-bristled brush.

Repeat the operation if the results are unsatisfactory. Rinse the treated surface thoroughly with water.

#### Cleaning

Brushes used to apply **WallGard Graffiti Remover Gel** can be cleaned with water.

#### **COVERAGE**

100 to 200 g/m<sup>2</sup> per coat, depending on the texture of the surface.

#### **PACKAGING**

5-kg buckets.

#### **STORAGE**

12 months in a cool, dry place in original sealed packaging.

### SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

**WallGard Graffiti Remover Gel** is irritant.

The use of protective gloves and goggles is recommended.

In cases of contact with eyes or skin wash with plenty of water and, if necessary, seek medical attention. For further and complete information about the safe use of our product please refer to our latest version of the Material Safety Data Sheet.

PRODUCT FOR PROFESSIONAL USE.

#### WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every

# **TECHNICAL DATA (typical values)**

PRODUCT IDENTITY	
Consistency:	liquid gel
Colour:	yellow
Density (g/cm³):	0.05
Storage:	12 months in original sealed packaging
Hazard classification according to ECC 1999/45:	irritant. Before using refer to the "Safety instructions for preparation and application" paragraph and the information on the packaging and Safety Data Sheet
Inflammability:	no
Customs class:	3814 00 90
APPLICATION DATA	
Waiting time before removing:	5 to 10 minutes at +20°C
Application temperature range:	+8°C to +35°C
Coverage (g/m²):	100 to 200

case, be taken as merely indicative and subject to confirmation after long-term practical application: for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application: in every case, the user alone is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the Technical Data Sheet, available from our web site www.mapei.com

All relevant references for the product are available upon request and from www.mapei.com



Using a high-pressure cleaner



Applying WallGard Graffiti Remover Gel on natural stone





